Metal protection by KRAUTOL - simply in the system



Project 4 Aluminium

Like zinc and copper, aluminium is a non-ferrous metal. An oxide layer may form on its surface, which makes it difficult for subsequent finish coatings to adhere to the surface. You should first apply a priming coat using KRAUTOL Zinc and Holding Primer for surfaces made of untreated aluminium, such as windows, doors, handrails and panelling. You can then paint the aluminium as you wish.

The KRAUTOL system solution



+

METALL SCHUTZ

GARLACE

12 Market

12 Market

13 Market

14 Market

15 Market

16 Market

17 Market

18 Market

or



Zinc and holding primer Special primer for non-ferrous metals and hard PVC

- Extra strong adhesion
- Fast-drying
- Easy to sand

Metal protection paint Protective layer With matt or glossy finish

Hammer blow paint Structured paint with hammer blow effect

- Exceptional protection against rust
- Excellent adhesion
- Resistant to weathering and UV light

KRAUTOL

Aluminium



Preparation and cleaning

Use a scrape test to determine adhesion in the old coat of paint. Carefully sand back any old coating layers and clean. Clean and degrease bare surface with nitro paint thinner. Use a non-woven cloth to work the solution into the entire surface and rub in with a clean cloth. You will find further information on BFS (German Federal Committee on Paint and Material Asset Protection) Info Sheet No. 6.



Primer

Prime the surface with KRAUTOL Zinc and Holding Primer once and leave to dry.



Prime and finish coat

Apply one or two layers of KRAUTOL Metal Protection or Hammer Blow Paint, depending on the desired surface appearance — glossy, matt or hammer blow effect. Ensure you apply a uniform coat covering the whole surface.

Note

Please note: do not coat anodised aluminium.



Use solvent-resistant rollers or brushes (China bristle).

When using the recommended products, please observe our further product, processing and safety instructions found on the product packaging and our technical info sheets, available from our website at www.krautol.de.

Our suggestions are standard solutions for a variety of applications. They are based on extensive experience as a paint manufacturer. We recommend obtaining professional advice if you wish to apply coating to objects under special conditions.

