



The project: rising damp in the base section

When not blocked correctly with horizontal or vertical damp proofing, rising damp from the ground creeps behind the rendering and paint, causing flaking in the base section. The base looks swollen and the paint peels away. You need to remove the damaged paintwork and rendering before restoring the base section. You must then allow the masonry to dry out properly since damage may arise again if you do not.

The optimum KRAUTOL system solution:



Tiefgrund Plus
Acrylic hydrosol for
façade levelling primer
coats



**Ultra1
Base Paint**
Façade base paint



KRAUTOL®

PROFESSIONAL

This is how it works: an optimum result in a few steps



Preparation and cleaning

Stop damp from penetrating and strip the old paintwork and rendering before applying new rendering and paint. Allow base to dry thoroughly after stripping.

Clean the base carefully with a pressure washer – do not use full pressure – and remove any dirt or stains completely.

Leave base to dry out completely after cleaning, so the subsequent primer can penetrate the façade more effectively.



Primer

Prime the base section with **Tiefgrund Plus**. This high-quality primer strengthens the surface, ensuring uniform absorption.

This brings the advantage that the façade paint dries evenly and adheres securely while less paint is consumed.

Allow façade to dry thoroughly again after priming.



Prime and finish coat

Pre-treat the base with **Ultra1 Base Paint** (diluted with a maximum of 10% water). The low viscosity of the paint ensures good penetration behaviour, thus achieving effective adhesion in the final coat.

Leave primer coat to dry out thoroughly. Then apply undiluted **Ultra1 Base Paint**.



Other façade projects

Simply scan the QR code with your smartphone or tablet and access additional information.

12/2017

Systematic façade protection